(54) Title: METHOD TO PRODUCE AROMATIC CARBOXYLIC ACIDS

Process flow diagram

(57) Abstract

A process to produce for example terephthalic acid is provided, the process including the steps of: providing a feed stream comprising a dialkyl substituted aromatic and an organic acid solvent: contacting the feed stream with a vapour stream, the vapour stream containing at least 50 % by volume oxygen and at an oxygen partial pressure of at least 1 psi, at a temperature between about 80 °C and about 130 °C, in the presence of a catalyst system comprising zirconium and cobalt, wherein the contacting is done in a stirred tank reactor; removing from the stirred tank reactor a vapour stream comprising the organic acid and water: condensing at least a portion of the organic acid and water from the vapour stream; separating at least a portion of the water from the organic acid separated from the vapour stream; returning at least a portion of the condensed organic acid back to the stirred tank reactor; continuously recovering from the stirred tank reactor a reactor product comprising a diacid substituted aromatic; isolating solid crystals of diacid substituted aromatic from the reactor product; and recovering from the solid crystals of diacid substituted aromatic a diacid substituted aromatic having a purity of at least 97 % by weight.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD TO PRODUCE AROMATIC CARBOXYLIC ACIDS

FIELD OF THE INVENTION

The invention relates to a method to produce aromatic dicarboxylic acids.

BACKGROUND TO THE INVENTION

U.S. patent No. 3,299,125 suggests a catalyst system for production of aromatic diacids which utilizes a combination of two metals, one being cobalt, and a second being from a group which includes zirconium. This catalyst system is shown to be effective for oxidation of para-xylene to terephthalic acid at temperatures in the preferred range of 80 °C to 130 °C. This temperature range is considerably lower than that necessary using other catalyst systems. The oxidation is performed in a solvent such as acetic acid and water, and oxygen or air are bubbled through the reaction medium. At 120 °C, reaction times of 8 hours are necessary to achieve conversions of para-xylene to terephthalic acid of sixty to eighty percent. With the combination of cobalt and zirconium as the catalyst, the highest yield of terephthalic acid shown was 88%. This patent describes the advantages of the catalyst system as being the ability to eliminate halide promoters from the catalyst system, thus significantly reducing metallurgy requirements in the reactor system.

U.S. patent No. 3,700,731 suggests a cobalt-catalyzed oxidation of para-xylene wherein the reaction is performed in a continuous stirred tank reactor with hold-up times on the order of 240 minutes, with a constant withdraw of product and recycle of unreacted feed and partially oxidized intermediates. The pressure of the reaction system is such that all of the reactants are

kept in the liquid phase, and air or air enriched with
oxygen up to 50% is preferred as the oxidant. The product
removed from the reactor is highly impure, with
terephthalic acid crystal purities of about 85%, and a
large quantity of partially oxidized intermediates
dissolved in the liquid phase. Terephthalic acid is
removed from the reactor product by filtering crystals
from a cooled reactor product, and then recycling the
liquid back to the reactor. The filtered crystals are
"digested" by contacting with a solvent such as acetic
acid at a temperature of 200 °C to 300 °C for about ten
minutes or longer, and then filtration of the digested
crystals at about 100 °C and washing with hot water or
acetic acid. These process operations result in a rather
large recycle stream of partially oxidized intermediates
to the oxidation reactor. A final terephthalic acid
product is said to be 98 to 99% pure with a yield based
on the starting para-xylene of 95% (molar). While the
oxidation of para-xylene to terephthalic acid is highly
exothermic, this patent is silent about how the oxidation
reaction is cooled. Although adequate cooling of the
stirred tank reactor can be achieved in a laboratory
environment, it is a significant factor in design of the
commercial reaction system because the produced
terephthalic acid is sparingly soluble in the reaction
solution. Crystals can therefore precipitate on heat
exchange surfaces if temperatures of the heat exchange
surfaces are significantly less than the temperature of
the reaction mixture, resulting in ineffective heat
removal.

The vast majority of commercially available
terephthalic acid is produced by improved versions of
US patent No. 2,833,816, which suggests a catalyst
combination of cobalt and manganese salts and a halide
promoter, for example bromine. In this system, para-

xylene is contacted with air in an acetic acid medium at temperatures in the range of 170 °C to 210 °C, and so-called "crude" terephthalic acid is produced. Over time, these systems have been improved to the point where typical crude terephthalic acid purities of 98-99.5% are produced in yields of roughly 95-96% molar based on para-xylene feed with oxidizer contact times of 45-90 minutes. However, this system suffers from significant acetic acid decomposition in the range of 5-10 lb/100 lb of terephthalic acid produced. In addition, the acetic acid and halide promoters are highly corrosive, necessitating the use of higher metallurgy, namely titanium. The contributions of acetic acid losses and titanium metallurgy significantly increase manufacturing costs.

US patent No. 5,523,474 suggests a catalyzed system with bromine promotion for para-xylene oxidation in an acetic acid medium. The reactor design is a so-called liquid oxygen reactor (LOR) which utilizes oxygen-enriched air in purities of 50-100% oxygen by volume. The benefits claimed include lower acetic acid decomposition and reduction in premature reactor shutdowns. While the patent describes the bromine-promoted system which requires titanium metallurgy, it fails to address the significant flammability concern associated with the incompatibility of oxygen-enriched air and titanium as is well known in industry and indicated in National Fire Protection Association 53 Guide on Fire Hazards in Oxygen-Enriched Atmospheres 1994 Edition.

For each of the oxidation techniques discussed above, after isolation the resulting terephthalic acid solids are generally referred to as "crude" terephthalic acid. The crude terephthalic acid can be up to 99.5% purity, with the primary impurities being 4-carboxybenzaldehyde (hereafter referred to as 4-CBA), para-toluic acid (hereafter referred to as pTA), and colour containing

species. Such a product is not of sufficient purity to be used directly for polyester fiber or bottle resins without additional purification, most typically by hydrogenation and re-crystallization. An example of such

5   a purification technique is US patent No. 3,584,039.

There is also significant commercial interest in production of isophthalic acid by oxidation of meta-xylene. Isophthalic acid is typically produced by processes similar to those used for terephthalic acid.

10   It would be desirable to have a process to produce these dicarboxylic aromatics wherein high para-xylene yields and conversions are obtainable, wherein titanium equipment is not required, and wherein solvent oxidation is decreased. It is therefore an object of the present

15   invention to provide an improved process for production of aromatic diacids having high yields and conversions, high crystal purities and reduced solvent decomposition losses are achieved, and reflux cooling can be utilized in a low temperature oxidation reaction system.

20   It is an object of a preferred embodiment of the present invention to provide an improved process for production of terephthalic acid, isophthalic acid, and mixtures of terephthalic acid and isophthalic acid.

SUMMARY OF THE INVENTION

25   This and other objects are achieved by a process to produce diacid substituted aromatics in a purity of at least 97%, the process comprising the steps of: providing a feed stream comprising the dialkyl substituted aromatic and an organic acid solvent; contacting the feed stream

30   with a vapour stream, the vapour stream containing greater than 50% by volume oxygen, at an oxygen partial pressure of at least 1 psia, at a temperature between 80 °C and 130 °C, in the presence of a catalyst system comprising zirconium and cobalt, wherein the contacting

35   is done in a stirred tank reactor; removing from the

stirred tank reactor a vapour stream comprising organic
acid and water; condensing at least a portion of the
organic acid and water from the vapour stream; separating
at least a portion of the water from the organic acid .
solvent separated from the vapour stream; returning at
least a portion of the separated organic acid back to the
stirred tank reactor; continuously recovering from the
stirred tank reactor a reactor product comprising a
diacid substituted aromatic; isolating solid crystals of
diacid substituted aromatic from the reactor product; and
recovering the crystals of diacid substituted aromatics
having a purity of at least 97% from the crystals
contacted with the fresh solvent. Use of oxygen or
significantly enriched air in the practice of the present
invention along with reflux cooling by removing solvent
vapours, and returning a portion of the condensed
solvent, provides an effective partial pressure of oxygen
for the oxidation reaction and avoids the presence of
heat exchange surfaces in the reactor. Removal of water
from the reflux provides an effective way to purge water
created by the oxidation reaction.

The process also preferably includes a step wherein
the isolated solid crystals of diacid substituted
aromatics are contacted with fresh solvent at a
temperature of between 150 °C and 250 °C for about 10 to
60 minutes. The fresh solvent is preferably water or an
organic acid which does not have a significant
concentration of oxidation byproducts in the solvent.

In a preferred embodiment, the alkyl substituted
aromatic is para-xylene, which is oxidized to
terephthalic acid and/or meta-xylene, which is oxidized
to isophthalic acid.

- 6 -

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a process flow diagram of a process for manufacturing aromatic carboxylic acids utilizing the present invention.

FIG. 2 is a graph showing calculated pressures of operation relating to example 9.

DESCRIPTION OF A PREFERRED EMBODIMENT

The method of the present invention utilizes an oxidation catalyst which has been found to be particularly effective for oxidation of aromatic alkyl groups to carboxyl groups. The catalyst system is a combination of a cobalt and a zirconium species. The cobalt and the zirconium may be in any form that is soluble in the reaction medium. Examples of such soluble forms include: organic acid salts, basic salts, complex compounds, and alcoholates. The amount of cobalt is generally between 0.01 and 1 molar in the reaction solution. The ratio of cobalt to zirconium is preferably not greater than 15:1 and more preferably between 10:1 and 5:1 molar. The catalyst can be added to the reaction mixture with the reactants or separately. The catalysts are preferably recycled from the solution of reactants by recycling the solution after the desired products have been removed by, for example, precipitation and/or filtration.

Other metals and promoters may be present in the catalyst system of the present invention, but the two metal system has been found to be effective. For example, halide promoters may be included, but it has been found that increases in activity are offset by greater metallurgy requirements. The absence of halide promoters is therefore preferred.

Referring now to FIG. 1, the species oxidized by the invention of the present invention is a dialkyl substituted aromatic provided to reactor (1). The dialkyl

substituted aromatic may be combined with the catalyst
materials, or the catalyst materials could be added to
the reactor separately. Para-xylene and meta-xylene are
especially preferred dialkyl substituted aromatics

5   because the resultant products are commercially valuable.
Mixtures of para-xylene and meta-xylene are also
commercially useful. Ethylbenzene and toluene can also be
contained in unpurified xylene streams. Various oxidation
intermediates of the above substituted aromatics could

10   also be used as starting feed materials, for example
para-toluic acid, para-tolualdehyde, or
4-carboxybenzaldehyde in the case of terephthalic acid
being the desired product. The feeds of the present
invention are provided in a solution with an organic acid

15   solvent in stream (a). Preferable organic acids include
organic acids having from two to four carbons with one
carboxyl group. The most preferred solvent is acetic acid
due to its vapour pressure at preferred reactor
temperatures, and its solvent capabilities. These organic

20   acids are solvents for reasonable concentrations of the
feed components, the catalyst system components, and the
intermediate products. The feed is preferably provided in
a solution of between 5 and 25 weight percent.

The dialkyl substituted aromatic is oxidized by a

25   vapour (b) initially containing at least 50% by volume
oxygen which is added to reactor (1) in vapour (b), at an
oxygen partial pressure of between 1 psia and 20 psia and
preferably between 3 and 15 psia. More than 50% by volume
oxygen is required so that the total pressure of the

30   reaction system can be low enough to allow reflux cooling
of the reaction system at temperatures of between 80 °C
and 130 °C, and more preferably of between 110 °C and
120 °C. The reflux cooling is a result of vaporization of
liquid phase components due to boiling and gas stripping,

35   creating vent stream (c). Reflux cooling results in a

uniform reaction temperature, the only differences in
temperature throughout the reactor being attributable to
static head and some local differences in compositions of
the solution. Further, reflux cooling eliminates cooling
surfaces within the reaction vessel. It is important to
eliminate cooling surfaces within the reaction vessel
because the oxidized products of the present invention
would tend to precipitate on the cooling surfaces and
foul the surfaces. Further, the uniform temperatures of
the present invention are desirable because uniform
reaction temperatures reduce undesirable side reactions.
The vapour stream (b) may be sparged into a liquid level
in a reactor, and the noncondensable vapours in stream
(c) from the reactor are either recycled or vented, but
the condensable solvent and water vapours in the vent
stream (c) are condensed in heat exchanger (2) for
recovery. A portion of the condensed liquids may be
returned to the reactor, while a portion may also be
directed to a solvent recovery system (3) for removal of
water from the solvent/water mixture.

The reaction of the present invention takes place in
a stirred tank reactor (1) with an essentially continuous
addition of reactants and withdrawal of products. Product
purities increase considerably when an essentially
continuous stirred tank reactor is utilized as opposed to
a batch or plug flow reactor. Useful reactors may have
baffles to improve contact of the sparged vapours with
the liquids in the reactor, thus not being a perfect
stirred tank reactor. But a significant portion of the
volume is preferably subjected to significant back mixing
and agitation, for example, with an impeller or jets.
Because halide promoters are not necessary and the
reaction is performed at relatively low temperatures, the
corrosivity of the reaction medium is not particularly
high. This allows use of stainless steel metallurgy as

the primary material of contact. Use of stainless steel
is advantageous over titanium because of cost and safety
in high oxygen concentration environments. For economic
reasons, the stainless steel can be constructed as a
inner cladding as the material of contact with a less
expensive outer layer of carbon steel. The reactor design
must also effectively provide for nearly complete oxygen
consumption below the liquid/gas interface. Nitrogen can
be injected in the vicinity of the liquid/gas interface
in a quantity rendering the vapour phase gas mixture non-
flammable. If desired, after dilution with nitrogen the
unconsumed oxygen (f) can be contacted with the feed
streams in optional pre-reactor (10) to provide nearly or
fully complete oxygen utilization.

The oxidation of the alkyl aromatic with the oxygen
stream results in production of reaction water. This
reaction water may be accumulated in the system to a
concentration less than 15 weight percent and preferably
between 3 and 10 weight percent. It has been found that
the catalyst system of the present invention is
surprisingly sensitive to the presence of water in
greater amounts. Some water may also be included in the
feed stream to supplement the reaction water present to
control solubility of the reactants, or to control the
temperature and cooling of the reactor.

The unvaporized portion of the reactor contents
containing both liquid and solid are essentially
continuously withdrawn as stream (d) and sent to a
suitable solid/liquid separator (4), which produces
solids (g) containing aromatic carboxylic acid crystals
with some solvent and mother liquor (h). The solid/liquid
separation device effectively isolates the solid crystals
from the liquid, and can in some cases also be provided
with means to wash the crystals with a suitable solvent.
The temperature at which the solid/liquid separation is

performed is preferably between 30 °C and 130 °C and more
preferably between 50 °C and 80 °C. Examples of
acceptable wash liquids include lower carboxylic acids
and aqueous solutions thereof, and water. Acetic acid is
most preferred, with an aqueous content less than 15%
water. Examples of suitable solid/liquid separation
devices include centrifuges and pressure filters. At
elevated temperatures and pressures when crystal rinsing
is the main objective, the Merco Disc-Nozzle centrifuge
(Dorr-Oliver, Milford, Connecticut) is a particularly
preferred low cost choice as the solid/liquid separation
device. After the solid crystals of the aromatic diacid
have been sufficiently washed, they can be furthered
exposed to an additional crystal soaking operation in
continuously stirred tank (5). If desired, additional
fresh solvent (i) is added. Fresh solvent may be hot
water, an organic acid, or a mixture thereof, but
preferably does not contain a significant amount of
partially oxidized alkyl aromatics. Most preferred is a
95/5 to 90/10 (w/w) acetic acid/water mixture. The
temperature at which the crystal soaking operation is
performed is preferably between 150 °C and 250 °C and
more preferably between 180 °C and 220 °C. The contact
time for the crystal soaking step is preferably between 5
and 120 minutes and more preferably between 10 and
60 minutes. The ratio of aromatic feed to solvent is
preferably between 1:1 (w/w) and 1:10 and more preferably
between 1:2 and 1:5. The resulting crystals are
discharged as a slurry (j). If the crystal soaking
operation is performed in the presence of acetic acid,
nitrogen is preferably used to provide an inert
environment, thus preventing oxidative degradation of the
acetic acid and discoloration of the aromatic acid
crystals.

When the aromatic feed is meta-xylene, the crystal
soaking operation can be performed at more mild
conditions, also in a continuously stirred tank. In this
embodiment of the present invention the temperature at
5   which the crystal soaking operation may be performed is
preferably between 120 °C and 220 °C and more preferably
between 140 °C and 200 °C.

After the initial crystal soaking is performed on the
aromatic carboxylic acid crystals, an additional
10   solid/liquid separation operation (6) can be performed in
separator (6), producing solvent (1) and crystal
stream (k). The crystal stream (k) can be furthered
processed in a crystal soaking/post oxidation vessel (7)
and/or dryer (9), or used without further processing if
15   desirable.

Where further processing in the crystal soaking/post
oxidation vessel (7) is utilized, any rinsing liquid used
in solid/liquid separation device (6) is preferably water
and the solid/liquid separation device should be equipped
20   with means for formation of a cake. In so doing, crystals
can be virtually freed from solvent contamination and
subsequently redispersed in an aqueous medium. Such an
operation is particularly preferred in the case of
isophthalic acid. The temperature at which the
25   solid/liquid separation may be performed is preferably
between 50 °C and 180 °C and more preferably between
80 °C and 130 °C. These temperature ranges have the
particular advantage of preventing the re-deposition of
oxidation intermediates such as meta-toluic acid and
30   3-CBA onto the isophthalic acid crystals.

When utilizing a continuously stirred vessel as the
crystal soaking/post oxidation vessel (7), the aromatic
diacid crystals can be contacted with air (n) as a means
of soaking the crystals and further oxidizing oxidized
35   intermediate impurities, in the case of isophthalic acid,

namely 3-CBA and meta-toluic acid. The temperature at
which the post-oxidation/crystal soaking operation is
performed is preferably between 120 °C and 220 °C and
more preferably between 150 °C and 200 °C. The contact
time for the post-oxidation/crystal soaking step is
preferably between 5 and 120 minutes and more preferably
between 10 and 60 minutes. The ratio of aromatic feed to
water is preferably between 1:1 (w/w) and 1:10 and more
preferably between 1:2 and 1:5 which can be adjusted by
addition of water (o). Upon completion of the post-
oxidation operation, the wet aromatic diacid crystals (m)
are isolated by a final solid/liquid separation and rinse
in separator (8), producing a wet aromatic diacid (p),
recovered solvent (q), and dried in dryer (9) to produce
an aromatic diacid (r), which, in the practice of the
present invention, will have a purity of greater than 97%
by weight. The temperature at which the solid/liquid
separation may be performed is preferably between 50 °C
and 180 °C and more preferably between 80 °C and 130 °C.
The post-oxidation step is found to be particularly
effective in production of isophthalic acid due to the
relatively high solubility of each of the meta isomers in
water. This high solubility lowers the required
operation/soaking temperature, allowing prevention of
colour body formation. No catalyst addition is required
in the post-oxidation step and the resulting isophthalic
acid product can be utilized directly in polyester
applications without further purification.

It should be noted that such a post-oxidation
operation can also be performed on terephthalic acid and
blends of terephthalic acid and isophthalic acid for
further reductions in impurities. Such an operation can
provide a product useful for some polyester applications
which require less stringent specifications on oxidation
intermediates and colour bodies.

Portions of organic acid streams (e), (h), (l), and
(q) can be either returned to reactor (1) or sent to
solvent recovery and dehydration system (3). The solvent
dehydration system (3) produces stream (s) (mainly
water), stream (t) (mainly purified acetic acid), and
stream (u) (mainly heavy ends residue and catalysts for
recovery).

EXAMPLE 1

A 316 stainless steel reactor was operated with
continuous feed addition and product removal at
temperatures between about 110 °C and 130 °C with
residence times of one to two hours, and a feed stream of
5 to 20 weight percent para-xylene in acetic acid with a
catalyst system of zirconium acetate [ZrO*(AcO)$_2$] and
cobalt acetate with cobalt concentrations of 0.05 to
0.15 molar, and a cobalt to zirconium molar ratio of 7:1.
The reactor was cooled with cooling coils and air was
sparged into the reactor through a subsurface diptube.
Acetic acid solution containing the catalyst and para-
xylene feed were delivered via a positive displacement
metering pump and product was continuously removed via
pulsed flow through a control valve in the bottom of the
reactor. Gas feed rates were monitored with mass flow
controllers. The pressure was maintained at about
240 psia. Water was added to the feed in concentrations
of up to 5% by weight in some runs. The reactor was
provided with an air driven gas dispersing impeller.

While the temperature was adequately controlled via
cooling coils, upon inspection of the reactor internals,
it was observed that dramatic fouling occurred on the
cooling coils. It is inferred that such fouling would
render commercial system inoperable, necessitating use of
evaporative cooling for extended operation.

The product from the continuous reactor was cooled to
about 50 °C, and precipitate was collected on a filter.

- 14 -

The precipitate was prepared for analysis by combining
the precipitate with 95:5 (w/w) acetic acid/water at
110 °C for a time period of 30 minutes. The resultant
crystals were analyzed and purities of terephthalic acid
5   of up to 97% percent by weight were produced, with the
most significant impurities being para-toluic acid and
4-CBA. Samples of the vent gas were regularly analyzed by
gas chromatography for oxygen (O_2), carbon monoxide (CO),
and carbon dioxide (CO_2). Liquid and solid products were
10   analyzed with HPLC using a 25 cm x 4.6 mm C18 column with
a water/acetonitrile/methanol gradient elution program.

Results from the experiments are reported in Table 1.
Methyl group conversion is defined as:

$$\frac{\text{mol methyl group consumed}}{\text{mol methyl group charged}}$$

and was computed from vent gas analysis as follows
15   (LPM = litres per mole):

$$\frac{\dfrac{(O_2 \text{ uptake from air- } O_2 \text{ used in } CO_2) \text{ LPM}}{22.4 \text{ L/mol} * 1.5 \text{ mol } O_2/\text{methyl group}}}{\dfrac{\text{g xylene/min in feed}}{106.1 \text{ g/mol} * 2 \text{ methyl groups/xylene}}}$$

where the GC based vent gas analysis was used to
determine the oxygen, carbon monoxide, and carbon dioxide
concentrations in the vent gas. The burn rate is defined
as:

$$\frac{(CO + CO_2) \; mol \; in \; vent}{8 \; mol \; Cox/mol \; xylene}$$

mol PX converted in feed

where the vent gas analysis was again used to compute the
carbon oxide production rate and the xylene conversion
was computed from the conversion described above. All
combustion products were allocated to the xylene in the
feed. An alternate assumption of acetic acid burning
would result in a different number differing only by the
carbon content of the molecules. Overall vent gas
concentrations of carbon oxides ($CO+CO_2$) were about 0.8%.

In a specific example, the reactor was operated at
120 °C and 240 psia with a catalyst concentration of
0.137 molar cobalt and a 7:1 ratio of Co/Zr. Para-xylene
in the feed was 9 percent by weight. The liquid phase
holdup time (residence time) in the reactor was
120 minutes. Results are shown in Table 1. For this
example, the methyl group conversion was 88% and about
1.7% of the para-xylene molecules were lost in the vent
gas. This corresponds to a reaction selectivity of 98.3%
based on para-xylene, given the assumption of negligible
acetic acid decomposition. If some acetic acid is
decomposed in the reaction, the selectivity should
actually be a higher value. The rinsed crystals from this
example were 96.6% purity and contained 2.2% para-toluic
acid and 1.1% 4-CBA. The crystals were a bright white,
fine powder.

EXAMPLE 2 (comparative)

A batch oxidation was carried out in the apparatus
described in Example 1 at 120 °C and 290 psia by charging
the autoclave with a mixture of 13% para-xylene in acetic
acid. Cobalt acetate was added at a concentration of

0.1 molar to the acetic acid with a cobalt to zirconium
ratio of 7:1 (molar). The oxidation was performed by
starting a mixed nitrogen/air flow and then backing out
the nitrogen as the catalyst became activated. The

5   oxidation reaction was run for about 1.5 hours after
which air addition was ceased. While at 120 °C, the
mother liquor was drained from the vessel through a
porous frit on the bottom of the vessel. Then hot acetic
acid was used to re-slurry and wash the crystals at

10   120 °C for about 5 minutes. After drying, the resulting
terephthalic acid crystals had a purity of about 84.6%
with 5.7% 4-CBA and 9.7% pTA. With the unsteady nature of
the experiment, an accurate gas phase analysis could not
be obtained.

15   EXAMPLE 3

       An oxidation reaction was performed in the apparatus
used in Example 1. The reaction pressure was lowered to
55 psia and the vessel was operated at 120 °C with a
120 minute residence time. The cobalt catalyst

20   concentration in glacial acetic acid was 0.1 molar with a
7:1 Co/Zr ratio. With a vent oxygen concentration of
4% (v/v), an oxygen partial pressure in the dry vent gas
of only 2.2 psia is obtained. As shown in Table 1, the
conversion was 32.4% and the aromatic burn rate was 4.6%.

25   Under these oxygen starved conditions, the aromatic burn
rate was significantly higher and very few solids were
present in the reaction product indicating that only a
small fraction of the product was converted to
terephthalic acid.

30   EXAMPLE 4

       An oxidation reaction was performed as in Example 1
with a mixture of 95:5 (w/w) para-xylene/meta-xylene at
13% in glacial acetic acid. The catalyst was 0.1 molar
cobalt with a Co/Zr ratio of 7:1. Temperature and

35   pressure were again 120 °C and 240 psia with a

108 minutes holdup time. The product of this reaction
were crystals of a mixture of terephthalic acid and
isophthalic acid, with a diacid purity of 93.3%. The
remaining composition of the crystals was comprised

5   largely of 6.7% pTA and 2.0% 4-CBA and low levels of mTA
and 3-CBA. As shown in Table 1, the conversion was 95.1%
and the aromatic burn rate was 1.2%, indicating a xylene
selectivity of 98.8%, assuming no acetic acid
decomposition. The crystals were a bright white, fine

10   powder.

EXAMPLE 5

An oxidation reaction was performed as in Example 4
with 100% meta-xylene. The unit was operated with a
115 minute holdup time at 120 °C and 240 psia. The

15   catalyst was 0.1 molar cobalt acetate and a molar ratio
of cobalt to zirconium of 7:1. As shown in Table 1, a
high methyl group conversion was obtained, suggesting
that the catalyst system is slightly more active with
meta-xylene than para-xylene. The burn rate was 1.5%,

20   indicating a selectivity of 98.5% based on meta-xylene.
The product isophthalic acid crystals were 98.8% pure,
indicating a significantly higher purity than in the case
of terephthalic acid. The crystals were a bright white,
fine powder.

25   EXAMPLE 6 (comparative)

A halide promoted oxidation was performed to compare
the relative burning losses of the two types of catalyst
systems. A Hastalloy C reactor was constructed similarly
to the stainless steel unit described in Example 1 and

30   was operated in a semi-batch fashion with an initial
charge of acetic acid and catalyst (Co/Mn/Br). To avoid a
high initial concentration of reactant, para-xylene was
fed continuously to the reactor at a rate of 70 g/hr. The
catalyst make up was 0.52 g of manganese acetate tetra-

35   hydrate, 0.18 g of cobalt acetate tetrahydrate, and

0.29 g of 48% HBr solution dissolved in 280 g of acetic
acid containing 17.5 g of water. The oxidation was run at
205 °C and 420 psia with the catalyst and solvent
initially charged to the reactor. After the feed of para-
xylene was completed, the temperature was lowered to
185 °C and the oxidation was completed with an additional
15 minutes of post-oxidation to scavenge any remaining
partially oxidized species in the mother liquor and to
partially age the crystals. Results in Table 1
demonstrate essentially complete conversion of the para-
xylene with burning losses of 3.6%. In this case, it is
known that the burning losses may be attributed to both
para-xylene and acetic acid. In comparison with
Examples 1, and 3-5, the losses are greater than twice
the amount of losses of the present invention.

EXAMPLE 7

The manner of oxidations demonstrated in examples 1,
4, and 5 produce crystals which are amenable to further
purification by exposing it to a higher temperature wash
stream for a time sufficient to allow partial dissolution
and re-precipitation of the crystals.

A sample of oxidation product from Example 1 was
combined with acetic acid with a ratio of acetic acid to
terephthalic acid of 9:1 and heated to 200 °C in a
continuously stirred reactor with a blanket of N_2 for a
holdup time of 30 minutes. The resulting slurry was
cooled to approximately 100 °C and filtered. The starting
material had a purity of 91.7% terephthalic acid, with
5.8% pTA and 2.9% 4-CBA. After the crystal soaking step,
the crystal purity was 98.4% terephthalic acid, with
0.88% pTA and 0.72% 4-CBA. The crystals were a bright
white, fine powder, with apparently so significant change
versus the starting material.

EXAMPLE 8

A sample of oxidation product from Example 5 was
combined with acetic acid with a ratio of acetic acid to
isophthalic acid of 9:1 and heated to 200 °C in a
continuously stirred reactor with a blanket of N_2 for a
holdup time of 30 minutes. The resulting slurry was
cooled to approximately 100 °C and filtered. The starting
material had a purity of 98.8% isophthalic acid, with
0.92% mTA and 0.24% 3-CBA. After the crystal soaking
step, the crystal purity was 99.98% isophthalic acid,
with none detected mTA and 0.02% 3-CBA. The crystals were
a bright white, fine powder, with no significant change
versus the starting material.

EXAMPLE 9

The need to operate the main oxidizer at low
pressures so that reflux cooling can be utilized is most
easily demonstrated with computer simulation. An
Aspen 9.3 simulation using a RSTOIC block operated
adiabatically was used to model the main oxidizer. The
effluent from the RSTOIC block was then adiabatically
flashed to generate a vapour and liquid stream. To avoid
the complication of coupling the condensed overhead
product with an acetic acid dehydration column, the
reflux, containing over 20% water, was simply returned to
the reactor. The liquid portion from the flasher was
removed as product. The vapour portion leaving the
flasher was cooled and the liquid condensate was returned
to the reactor. The oxidizer model was operated at 99.9%
para-xylene conversion with a 3% burning loss to carbon
dioxide. Air was fed so that the vent gas contained 3.5%
oxygen on a dry gas basis and the feed contained 15%
para-xylene and 5% water in acetic acid. Results from the
simulations conducted at a series of pressures are
presented in Figure 2. The results demonstrate that to
keep an operable oxygen partial pressure (>1 psia oxygen

partial pressure and preferably greater than >10 psia) at
temperatures lower than 130 °C, an oxygen rich feed is
required to allow cooling of the reactor by boiling. The
higher pressures required with air to provide the
necessary oxygen partial pressure would prevent boiling
of the reactor contents.

Table 1: Results from Examples

Example	Targeted Product[1]	Conversion	Burn Rate	% diacid	% toluic acid	% CBA
1	TPA	96.6	1.7	96.6	2.2	1.1
2	TPA	NA	NA	84.6	9.7	5.7
3	TPA	32.4	4.6	NA	NA	NA
4	TPA/IPA mixture	95.1	1.2	93.3	6.7	2.0
5	IPA	99.2	1.5	98.8	0.92	0.24
6	TPA	101.5	3.6	99.5	0.45	0.06
7	TPA	NA	NA	98.4	0.88	0.72
8	IPA	NA	NA	99.98	nd	0.02

[1] TPA stands for terephthalic acid, IPA stands for
isophthalic acid, and nd stands for none detected. For
TPA, impurities listed are 4-CBA and pTA. For IPA,
impurities listed are 3-CBA and mTA.
NA = Not Analyzed.

- 21 -

C L A I M S

1. A method to produce an diacid substituted aromatic in
a purity of at least 97%, the method comprising the steps
of:
     providing a feed stream comprising a dialkyl
5   substituted aromatic and an organic acid solvent:
     contacting the feed stream with a vapour stream, the
vapour stream containing at least 50% by volume oxygen
and at an oxygen partial pressure of at least 1 psi, at a
temperature between about 80 °C and about 130 °C, in the
10   presence of a catalyst system comprising zirconium and
cobalt, wherein the contacting is done in a stirred tank
reactor;
     removing from the stirred tank reactor a vapour
stream comprising the organic acid and water:
15   condensing at least a portion of the organic acid and
water from the vapour stream;
     separating at least a portion of the water from the
organic acid separated from the vapour stream;
     returning at least a portion of the condensed organic
20   acid back to the stirred tank reactor;
     continuously recovering from the stirred tank reactor
a reactor product comprising a diacid substituted
aromatic;
     isolating solid crystals of diacid substituted
25   aromatic from the reactor product; and
     recovering from the solid crystals of diacid
substituted aromatic a diacid substituted aromatic having
a purity of at least 97% by weight.
2. The method of claim 1 wherein the mass ratio of
30   cobalt to zirconium is greater than about 10.

- 22 -

3. The method of any one of claims 1-2, wherein the temperature of the stirred tank reactor is between 110 °C and 120 °C.

4. The method of any one of claim 1-3, wherein the diacid aromatic is a xylene.

5. The method of claim 4 wherein the xylene is para-xylene.

6. The method of any one of claims 1-5, wherein the organic acid is acetic acid.

7. The method of any one of claims 1-6, wherein the concentration of the dialkyl substituted aromatic in the organic acid is between 5 and 25 weight percent based on the total feed.

8. The method of any one of claims 1-7, wherein the feed stream further comprises between 3 and 15 percent by weight water.

9. The method of any one of claims 1-8, wherein the zirconium is in the form selected from the group consisting of organic acid salts, basic salts, complex compounds, and alcoholate.

10. The method of any one of claims 1-9, wherein the cobalt is in the form selected from the group consisting of organic acid salts, basic salts, complex compounds, and alcoholate.

11. The method of any one of claims 1-10, wherein the feed stream further comprises a recycle of partially oxidized aromatics.

Figure 1. Process flow diagram

Equipment list:
1-Oxidation reactor
2-Heat exchanger
3-Acetic acid recovery/dehydration
4-Solid/liquid Separation
5-Crystal soaking vessel
6-Solid/liquid Separation
7-Crystal soaking/post-oxidation (optional)
8-Solid/liquid separation (optional)
9-drying (optional)
10-Pre-reactor (optional)

Figure 2: Computed pressure and temperature requires for an adiabatic boiling oxidation reactor using a 15% para-xylene feed containing 5% water in acetic acid.

| | Inter, onal Application No |
| | PCT/EP 98/08134 |

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6   C07C51/265   C07C63/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6   C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category°	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 3 562 318 A (BARONE BRUNO J ET AL) 9 February 1971 see claims 6,10; examples I,V,VI	1-11
Y	EP 0 754 673 A (ICI PLC) 22 January 1997 see claim 1	1-11
Y	GB 1 373 230 A (MITSUI PETROCHEMICAL IND) 6 November 1974 see page 1, line 68 - line 82; claim 1	1-11

☐ Further documents are listed in the continuation of box C.   ☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
15 April 1999	22/04/1999

Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Janus, S

Form PCT/ISA/210 (second sheet) (July 1992)

1

INTERNATIONAL SEARCH REPORT

information on patent family members

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 3562318	A	09-02-1971	BE	706159 A	07-05-1968
			DE	1668556 A	10-02-1972
			FR	1544331 A	
			GB	1215031 A	09-12-1970
			NL	6715161 A	13-05-1968
EP 0754673	A	22-01-1997	CA	2062063 A	08-09-1992
			CN	1064676 A,B	23-09-1992
			CN	1150945 A	04-06-1997
			DE	69214859 D	05-12-1996
			DE	69214859 T	27-02-1997
			EG	19876 A	30-06-1996
			EP	0502628 A	09-09-1992
			EP	0722927 A	24-07-1996
			ES	2093189 T	16-12-1996
			JP	5065246 A	19-03-1993
			MX	9200997 A	01-10-1992
			US	5563293 A	08-10-1996
			US	5527957 A	18-06-1996
			US	5679846 A	21-10-1997
			US	5877346 A	02-03-1999
			ZA	9201380 A	25-08-1993
GB 1373230	A	06-11-1974	NONE		